

TRANTER-SWEP SIZE CHART

Model	Corrugation	Port Diameter	Chevron Angle	Corrugation	Equivalent	Flow Area(m ²)	One Plate (Port Distance	Dimensions
GC008	2.2	φ30	51.2°129°	6.52	4.4	0.0002	0.08	640*60	715*125
GC16	1.9	φ55	60°118°	6	3.8	0.0004	0.16	592*135	700*250
GL13	3	φ67	58°120°	9	6	0.0007	0.13	592*135	714*248
GX12	3	φ67	85°115°	9	6	0.0007	0.13	592*135	714*250
GX18	3	φ67	85°115°	9	6	0.0007	0.18	822*135	941*248
GX26	3.3	φ105	85°115°	12	6.6	0.0012	0.26	779*226.5	941*384
GX42	3.3	φ105	85°115°	12	6.6	0.0012	0.42	1189*226	1352*385
GC26	4	φ105	66°114°	14.5	8	0.0014	0.26	79*226	941*384
GX51	3.25	φ145	85°115°	12	6.5	0.0015	0.51	1143*300	1354*507
GC51	4	φ145	60°118°	14.5	8	0.0019	0.51	1143*300	1352*505
GC54									
GX64	3	φ152	85°115°	9	6	0.0014	0.64	1320*281	1552*506
GX91	3	φ152	85°115°	9	5.8	0.0014	0.91	1800*282	2032*506
GX118	2.9	φ152	85°115°	9	5.8	0.0014	1.18	2280*285	2512*506
GC60	4.4	φ216	63°115°	15	8.8	0.0029	0.6	910*420	1196*700
GX60	3.5	φ194	85°115°	12	7	0.0023	0.6	910*420	1196*704
GX100	3.5	φ194	85°115°	12	7	0.0023	1	1490*420	1776*704
GX140	3.5	φ194	85°115°	12	7	0.0023	1.4	2070*420	2356*704
GX85	3.3	φ315	85°115°	11	6.6	0.003	0.85	1140*570	1528*942
GX145	3.3	φ315	85°115°	11	6.6	0.003	1.45	1720*570	2108*942
GX205	3.3	φ315	85°115°	11	6.6	0.003	2.05	2300*570	2688*942
GX265	3.3	φ315						2880*570	3268*942
GF187									
K71	4	φ115	122°	13.12	8	0.0018	0.75	1552.5*310	1730*487
K55	4	φ115	122°	13.12	8	0.0018	0.59	1237.5*310	1415*487
K34	4	φ115	122°	13.12	8	0.0018	0.37	832.5*310	1010*487
B063	3.2	φ300	60°123°	10 10.02	6.4	0.0025	0.66	1043*86	1414*854

B110	3.2	φ300	60°123°	10 10.02	6.4	0.0025	1.12	1523*4 86	1894*8 54
B134	3.2	φ300	60°123°	10 10.02	6.4	0.0025	1.35	1763*4 86	2134*8 54
B158	3.2	φ300	60°123°	10 10.02	6.4	0.0025	1.58	2003*4 86	2374*8 54
B205	3.2	φ300	60°123°	10 10.02	6.4	0.0025	2.05	2483*4 86	2854*8 54
TR9AL	3	φ200	90°180°	12.22 12	6	0.0019	1.55	2329*4 09	2591*6 70
TR9AV	3	φ200	90°180°	12.22 12	6	0.0019	1.22	1897*4 09	2159*6 70
TR9GN	3	φ200	90°180°	12.22 12	6	0.0019	0.89	1465*4 09	1727*6 70
TR9GL	3	φ200	90°180°	12.22 12	6	0.0019	0.56	1033*4 09	1295*6 70
P190	4.6	φ336	120	16.45	9.2	0.0042	1.9	2137*5 70	2544*9 84
P105	4.6	φ336	120	16.45	9.2	0.0042	1.05	1339*5 70	1746*9 84
SR2	2.6	φ63.5	6°180°90°	8.78 8.41	5.2	0.0007	0.2	700*180	838*298
SR3	3.65	φ73.9	80°180°	13.9/13 .86	7.3	0.0013	0.35	1022*2 62	1152*3 92
R5	5.4	φ101.4	120°	14.45	10.8	0.0019	0.527	1397*25	1556*420
SR6GL	3.8	φ102	80°180°	12.36/1 1.75	7.6	0.0017	0.56	1256*3 14	1418*4 76
SR6AG	3.8	φ102	80°180°	12.36/1 1.75	7.6	0.0017	0.9	1891*3 14	2053*4 76
R8GI	3.6	φ148	76°180°	13.5/13 .36	7.2	0.0018	0.75	1525*3 34	1737*5 46
SR9	5.3	φ200	50°180°	21/20.3	10.6	0.003	0.84	472*37	1744.5 *644.5
R8									
R10	5.4 9.6	φ197	180°	31.87	10.8	0.0059	1.2	1684*4 32	1986*7 12
R14	3.3	φ252.7	90°180°	3.5/13.5	6.6	0.0026	1.4	1792*512	1122*846
SR14GD	3.2	φ300	60°122.5°	10	6.4	0.0026	0.66	1043*4 86	1413*8 54
SFD13	4 3.5	φ74	180°	11.1	7	0.0008	0.13	620*15 0	744*270